

FS211 Clean-Fill®

Hygienic Filling & Closing Bench

When hygienic filling is your priority



There are still many laboratories and pilot plants that fill and close the heat-treated product in an open contaminated atmosphere. Moreover, the filling line has not been part of a CIP and/or SIP procedure. This will create unacceptable variations in the quality of your trials and doesn't give a representative simulation of an industrial process line. With the special designed Clean-Fill & Clean-Fill ESL, OMVE offers the widest range of filling benches for laboratories and pilot plants within the food industry. Different packaging can be filled and closed within the hygienic environment.

The Clean-Fill FS211 is a filler in stainless steel with a filling point. A foot pedal for filling the containers is controlled by an automatic hygienic valve. Included in the system is a temperature sensor at the coldest spot as well as a touch screen to display this temperature during sterilization. The condensate cooler ensures controllable cooling of the pressurized water or steam during sterilization

Unique Features

- Sterile Down flow filling bench
- Adjustable front window
- Minimum height of the unit, no need for disassembling
- Complete Stainless-Steel system
- Integrated in cleaning loop
- Aseptic control valves
- Larger versions ("Extended") available
- Different closing devices can be installed
- Integrated in sterilization loop
- TFT touch screen guidance during sterilization

Working principle

The OMVE Clean-Fill creates a class 100 working environment ensuring protection for (non-hazardous) products. The continuous down flow and over-pressure, created by the sterile air coming from the HEPA-filter, prevents inflow of contaminated air from outside the filling bench. The hygienic filling nozzle (is part of the cleaning and sterilization) is located inside the filling bench. The filling is controlled by the foot pedal. This gives you full freedom to handle the packaging with your hands and minimize contamination.

Filling Systems

FS



Standard accessories

- Extended Down Flow Cabinet (Ext.)
- Closing devices such as:
 - Crown Cork Sealer
 - Screw Cap Sealer (plastic caps)
 - Hot Sealer
 - Can Seamer
- Different heights filling point

For the FS211 only:

- UV lamp for disinfection
- Filling flow control
- Nitrogen Flush for packaging

Specifications

Name	Clean-Fill ESL	Clean-Fill ESL Extended
Product code	FS211	FS211 Ext.
Filters		
HEPA-Filter	H14 acc. to EN1822	H14 acc. to EN1822
Filling controlled by	Automatic foot pedal	Automatic foot pedal
Cleaning / Sterilization suitable	CIP / SIP	CIP / SIP
Materials		
Product line	SS AISI 316	SS AISI 316
Overall Dimensions		
LxWxH	1165x1003x1900mm [46x40x75"]	1915x1003x1900mm [76x40x75"]
Weight	200 kg	250 kg
Utilities required		
Water supply	2,5bar(g) 15°C [36psi 60°F]	2,5bar(g) 15°C [36psi60°F]
Electrical	220V / 1ph / 50Hz / 16A 220V / 3ph / 60Hz / 16A	220V / 1ph / 50Hz / 16A 220V / 3ph / 60Hz / 16A

Equipment Family

- Clean-Fill FS211 Down Flow Filling Bench with CIP & SIP possibilities
- Asepto-Fill FS212 Microbiological Isolated Filling Bench with CIP, SIP, Isolated filling environment & gamma radiated containers. For more information, ask for the Asepto-Fill brochure.
- Bag Filler FS218 Aseptic Bag Filler with CIP, SIP, Buffer tank and flow control.

Why OMVE

- ✓ OMVE is fully **specialized** in manufacturing R&D and Pilot plant equipment since 1993
- ✓ OMVE is the **preferred supplier** for the leading multinationals worldwide.
- ✓ OMVE Systems are designed and manufactures according to the **highest industrial standards**
- ✓ OMVE Systems have **2 years'** warrantee
- ✓ OMVE Systems are supplied with CE **certification**
- ✓ OMVE offers the **most comprehensive service** in the market