

# In-Line Sterilization

## HT223 Laboratory DSI System | HT323 Pilot Plant DSI System

The add-on Direct Steam Injection with flash tank system

Direct steam injection (DSI) requires highly accurate control of the steam that is injected in the product to ensure an accurate temperature. In the flash tank the product is rapidly cooled under vacuum. The flash tank pump will pump the product further through the system.

OMVE has designed a fully sanitary DSI with flash tank system that offers a high level of automation to make the operation very user-friendly. This unit can be added to an existing UHT system.

The system can be fully controlled by the HT220 or HT320 system. The nominal capacity ranges from 20L/hr up to 200L/hr.

## Features & Benefits

- User-friendly
- Aseptic design
- Automatic CIP/ SIP
- High level of automation
- Up to 20bar flash tank pump outlet pressure
- 0,2bar(a) vacuum for cooling in the flash tank

## Applications

- Baby food
- Plant-based protein drinks
- Dairy products
- Low viscosity drinks with small particles

## Working Principle

The HT223/ HT323 System gives the operator maximum flexibility in heating various liquid products with direct steam injection. It is possible to treat your product with different temperatures to simulate your industrial process.

During the typical operation, three processes can be distinguished: sterilization (SIP), production and cleaning in place (CIP).



## Optional Accessories

- Connection to the homogenizer
- External data logging
- Variable holding tubes
- Remote assistance

## Specifications

Product Code	HT223	HT323
Size	20L/hr or 50L/hr	20L/hr up to 200L/hr
Nominal / process flow rate	20L/hr (10-30L/hr) 50L/hr (30-80L/hr)	50L/hr / 30-90L/hr
Max. temperature steam	160°C [320°F]	160°C [320°F]
<b>DSI Heat Exchanger</b>		
Internal diameter/ connection	½"	½", ¾"
Max. particle size	1mm [0,08"]	1mm [0,08"]
Viscosity @ injection	Up to 500cPs	Up to 500cPs
<b>Materials</b>		
Product side	SS316	SS316
<b>Weights &amp; Dimensions</b>		
Weight	250kg [551lbs]	350kg [771lbs]
L x W X H	1050 x 1020 x 1450mm [41,3 x 40,2 x 57"]	1500 x 1300 x 2000mm [59 x 51,2 x 78,7"]
<b>Required utilities</b>		
Electrical	370-400Vac/ 3ph+N+E/ 50Hz/ 16A or 200-240Vac/ 3ph+E/ 60Hz/ 32A	
Steam for DSI	6-8 bar(g) [88 - 116psi]	



The HT223 and HT323 can be seamlessly integrated with other OMVE equipment.

OMVE Netherlands B.V.  
 Gessel 61  
 3454 MZ, De Meern  
 The Netherlands  
 Tel +31 30 241 00 70  
 sales@omve.com  
 omve.com

OMVE Americas Inc.  
 251 Main Street East, Suite L01  
 Milton, ON L9T 1P1  
 Canada  
 Tel +1 416 986 8442  
 sales@omve.com  
 omve.com

Lab & Pilot Equipment

